

## Electronic Product Reference Guide

PRODUCTS ► AND FEATURES ▼		A2 A2X A4	K1 K2 K8	KM10 KM15	T2	G2	GC30 GC31	GC35	GC51 GC52	GC55	KS	KX	CXIdp	DXIdp	IXIdp	RXIdp	XLdp	D1005PS	2084 2086 2089	2074 2174 2274	2032, 2036 2132, 2136 2232, 2236	
ACCURACY	0.05% and better																			● <sup>(1)</sup>		
	0.1% to 0.25%	●			●	●			●					●	●		●			●	●	●
	0.50%	●	●	●					●	●			● <sup>(2)</sup>	●	●		●					
	1.0% and above	●	●	●	● <sup>(3)</sup>	● <sup>(3)</sup>	●	●			●	●	●	●	●		●					
RANGES	Pressure Range (consult for other units)	Vac to 10,000 psi	Vac to 20,000 psi	Vac to 7,500 psi	Vac/30 psi to 20,000 psi	30 psi to 20,000 psi	0.25 to 25iw Vac to 1,500 psi	Vac to 9,000 psi	Vac to 7,500 psi 0 to 400iw	75 psi to 300	100 psi to 5,000 psi	100 psi to 5,000 psi	0.05 to 25 iw	0.05 to 50 iw	0.05 to 200 iw	0.1 to 50 iw	0.05 to 50 iw	Vac to 19,999 psi	Vac, 5 psi to 7,000 psi	Vac/15 psi to 20,000 psi	15 psi to 1,000 psi	
	Gauge	●	●	●	●	●	●	●	●		●	●						●	●	●	●	
	Absolute	●																		●		
	Differential						●		●	●			●	●	●	●	●					
OUTPUT SIGNALS	4-20mA	●	●		●	●		●	●	●	●	●	●	●	●	●	●				● <sup>(4)</sup>	● <sup>(4)</sup>
	Voltage (0-5, 0-6, 0-10, 1-5, 1-6, 2.5, 5, 0.5-4.5 Ratiometric)	●	○	○	●	●	●			○	○	○	○	○	●	●	○					
	mV/V (2, 3, 10, 20)		● <sup>(5)</sup>								●											
	Switch Output						●	●		●											●	●
ENCLOSURE RATINGS	Ingress Protection / NEMA	IP-66/67 (4, 6, 7, 9)	1, 4X	IP-66/67	IP-65/67 (4X)	IP-67 (4X)	IP-40	IP-65/67	IP-67 (4X)	IP-64	1, 4X	4X	1	1	4X	1	2	IP-54	IP-65	IP-65		
APPROVALS	RoHS			●		●	●						○									
	Hazardous Rating	●	●												●				●	●	●	

**NOTES:**

- (1) 0.05%
- (2) 0.4% and 0.8%
- (3) Includes temperature error
- (4) 2274 / 2232 /2236 w/XAO
- (5) K2 / K8

**KEY:**

- Available
- Consult Factory